378 Stealth Scorpion

Cut Resistance



ANSI/ ISEA 105-16 CUT LEVEL

18gg P-Aramid/ steel shell is cut resistant offering excellent protection

POLYURETHANE PALM

Lightweight polyurethane coated palm for a sure-grip

TOUCHSCREEN

Conductive coating on palm and fingers can be used on all touchscreen devices

TREATED WITH ACTIFRESH®

Treated with Actifresh® to kill bacteria and support freshness

SNUG-FITTING WRIST

Snug-fitting knit wrist keeps out dirt and debris

EN407 CONTACT HEAT INFORMATION

The En 407 Contact heat rating means that the glove is exposed to temperatures between + 100°C to + 500°C. The length of time is then measured for how long it takes the material on the inside of the glove to increase by 10°C from the starting temperature (approx. 25°C). 15 seconds is the minimum accepted length of time for approval. Contact heat rating level 2 means the glove is able to withstand contact of up to 250°C for at least 15 seconds before the inside of the glove becomes 10°C warmer.

3



CUT RESISTANCE

PRODU NAME	JCT # I I BRAND	378 SCORPION STEALTH	RATINGS I TECHNOLOGIES	EN407 ANSI EN388 ANSI -X1XXXX PUNCTURE 3X21E CUT
SIZE I PACK	AGED	S–XXL	ICONS	CUT RESISTANT
UPC	S 06553786290 M 06553786291 L 06553786292	10 XXL 065537862941	APPLICATIONS	Fabrication Construction General Purpose

BURNABY P 604 874 1105

F 604 875 9009 T 800 663 9509 CALGARY P 403 279 2262 F 403 236 7919 T 800 363 7462 **MISSISSAUGA** P 905 363 0727 F 905 363 0730 T 888 715 4299

